



# New Product Announcement

## Dunkirk Introduces New D250 Series of Commercial Boilers

Dunkirk is proud to announce the updated **D250 Steam** Commercial Boiler. In addition to the steam boiler, Dunkirk is proud to reintroduce an updated **D250 Water** Commercial Boiler as well. The D250 Series boilers are engineered to deliver dependable performance and improved efficiency for demanding commercial applications. Model sizes range from 360 MBH inputs to 1350 MBH inputs in 12 models each for the steam and water boiler offerings.

The **D250 Steam and Water Boilers** come with pre-assembled bases from the factory, including burner manifolds, burner orifices, gas valves, and electronic ignition - ensuring a simplified field installation process for contractors. Designed for ease of use, this model features a Plug ‘N Play harness and junction box, allowing for quick and straightforward setup with a factory-supplied color-coded wiring harness that connects all components seamlessly. To meet specific safety regulations, the **D250 Series** offers an optional CSD-1 package, which includes additional controls and safety devices to comply with CSD-1 standards where required.

Along with the updated series, the 300 MBH size is no longer offered. The following Dunkirk products will cover applications requiring that size of boiler. Steam boiler: PSB-299; Water boiler: WPSB-9D.

The capacities and ratings for the updated models are listed in the chart below:

	INPUT	OUTPUT	AHRI CERTIFIED RATINGS			
MODELS	CH Mode Max MBH	Gross MBH Water / Steam	Steam SQ Ft	Steam MBH	Water MBH	THERMAL EFFICIENCY Water / Steam
D250-400S/W	360	288 / 284	889	213	250	80% / 79%
D250-500S/W	450	360 / 356	1111	267	313	80% / 79%
D250-600S/W	540	432 / 427	1333	320	376	80% / 79%
D250-700S/W	630	504 / 498	1556	373	438	80% / 79%
D250-800S/W	720	576 / 569	1778	427	501	80% / 79%
D250-900S/W	810	648 / 640	2000	480	563	80% / 79%
D250-1000S/W	900	720 / 711	2222	533	626	80% / 79%
D250-1100S/W	990	792 / 782	2445	587	689	80% / 79%
D250-1200S/W	1080	864 / 853	2667	640	751	80% / 79%
D250-1300S/W	1170	936 / 924	2889	693	814	80% / 79%
D250-1400S/W	1260	1008 / 995	3111	747	877	80% / 79%
D250-1500S/W	1350	1080 / 1067	3334	800	939	80% / 79%

(Suffix S = Steam, Suffix W = Water)



**New Item Numbers and Trade Pricing:**

Newly created D250 Series SKUs will be added to the excel pricing files to be downloaded from the ECR Customer Web Portal at: <https://www.ecrcustomerportal.com>.

Units are available for ordering and subject to current lead time. If you have any questions regarding this product, please contact your Dunkirk Sales Manager, Dunkirk Representative or call 1-800-325-5479.

Sincerely,

A handwritten signature in black ink, appearing to read 'Bob Shea', is positioned above the typed name.

Bob Shea  
Executive Director of Sales  
ECR International