

Chilled/Hydronic Ductless Air Handlers

US Trade Price Book - 2021

Effective 8/9/21





CAW Ceiling Air Handler

CCP Ceiling Suspended Air Handler



WCP High Wall Air Handler

Comfort Where It Counts

www.emiretroaire.com



Customer Support Team

Volume Quotes: Sheila Henderson: (315) 731-4154 Email: sheila.henderson@ecrinternational.com

Customer Service: Phone: 800-325-5479 option #2 Fax: (315) 724-9319 Email Purchase Orders: ecrorderentry@ecrinternational.com Email Inquiries: customerservice@ecrinternational.com

Technical Support:

Phone: (800) 253-7900 Fax: (866) 432-7329 Email: technical.support@ecrinternational.com

Marketing Support: Phone: (800) 325-5479 Fax: (315) 733-1759 E-mail: marketing@ecrinternational.com


WWW.ECRCUSTOMERPORTAL.COM

Your On-line Access to:

- Order Status
- Invoices
- Statements
- RMA
- Serial Number Look-Up
- Literature

Table of Contents

CAWCassette Air Handler (CAW) Product InformationCAWFan Coil Descriptions (CAW)		4-10
DECODING CAW CAW CAW	Cassette Air Handler (CAW) Product Information Fan Coil Descriptions (CAW)	4 5 6 7
Comfortwave C	ceiling-Suspended (CCP) & High-Wall (WCP) Air Handlers	11-17
DECODING CCP & WCP CCP CCP WCP	Ceiling-Suspended (CCP) & High-Wall (WCP) Air Handler Decoding Ceiling-Suspended (CCP) & High-Wall (WCP) Product Information Fan Coil Descriptions (CCP) & (WCP) Ceiling-Suspended Air Handler (CCP) Trade Pricing High-Wall Air Handler (WCP) Trade Pricing	11 12 13 14 16
Terms & RMA I	Policy	18-19



* 24 Vac wall thermostat is sold separately.

* I/R Handheld Remote controller is included.





CAW Cassette Air Handlers

2-Pipe Chilled Water (Optional Electric Heat)

com

4-Pipe Chilled Water with Hydronic Heat

- 8,000 36,000 Btu/h Capacities
- 208-230 V/1 ph/ 60 Hz Standard
 - 115 V/1 ph/ 60 Hz Available
 - 220-240 V/1 ph/ 50 Hz Available
 - No De-rate for 115 V or 50 Hz
- 6 Nominal Capacities:
 - 8,000 Btu/h
 - 12,000 Btu/h
 - 18,000 Btu/h
 - 20,000 Btu/h
 - 33,000 Btu/h
 - 36,000 Btu/h
- 24 Vac Remote Thermostat Configuration
- Infrared Handheld Remote Control Option
 Remote Sold Separately
- Washable Return Air Filter(s)
- 2-Pipe Applications Allow for Optional Factory Installed Electric Heat:
 - 1 kW 8,000/12,000 Btu/h
 - 3 kW 18,000/20,000 Btu/h
 - 5 kW 33,000/36,000 Btu/h
- Supply-Discharge Air Louvers
 - 8/12 kBtu/h (Manually Adjustable)
 - 18/36 kBtu/h (Auto Sweep or Fixed Positions Stop)
- Factory Installed Condensate Pump (36 in Lift)
- Fresh Air & Branch Duct Knockouts

Warranty:

- Standard 1-year parts
- 5-year compressor warranty







Cassette Remote Control (Included with Infrared Option)

Shipping Weights lb (kg)					
	2-Pipe		4-Pipe		
Model	208-230 V & 220-240 V	115 V	208-230 V & 220-240 V	115 V	
CAW08	70 (31.8)	80 (36.3)	76 (34.5)	86 (39.0)	
CAW12	70 (31.8)	80 (36.3)	76 (34.5)	86 (39.0)	
CAW18	108 (49.1)	118 (53.5)	115 (52.2)	125 (56.7)	
CAW20	108 (49.1)	118 (53.5)	115 (52.2)	125 (56.7)	
CAW33	146 (66.4)	169 (76.7)	175 (79.4)	185 (83.9)	
CAW36	146 (66.4)	169 (76.7)	175 (79.4)	185 (83.9)	

Comfortwave Fan Coil Control Descriptions (CAW)

Unit / Control Type	Description
CAW Cassette (A) & (B) A - Wall Thermostat CAWA Unit - Thermostat is Not Included	Unit will not have the LED lights display on the facia. Choose 24 Vac, dry contact type thermostat. EMI equipment is compatible with most standard bimetal, digital electronic or power-stealing thermostats. Chilled Water Cooling Only - select a thermostat compatible with chilled water cooling system and the chilled water valve selected. Thermostat should have "R", "Y" and "G" terminals. Thermostat may also have a "C" terminal. Chilled Water with Electric or Hot Water (Hydronic) Heat - Select thermostat compatible with chilled water cooling and hot water or electric heating systems with water valve(s) selected. Thermostat should have "R", "Y", "W" and "G" terminals. Thermostat may also have "C" terminal. WHEN SELECTING WALL THERMOSTAT UNITS THEY ARE NOT CONVERTABLE TO OPERATE WITH AN IR REMOTE CONTROL
B - IR Handheld Remote CAWB Unit is shipped with the handheld IR remote	Implementation Implementation Implementation Implementa

	Comfortwave Cassette Air Handlers (CAW)	
ltem #	2-Pipe Fan Coil Cassette Air Handlers - No Heat	Tra
	Wall Thermostat Operation Only (24 Vac wall thermostat sold separately)	Pri
CAWA08A0A	8,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, Wall T-stat	\$3,
CAWA12A0A	12,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, Wall T-stat	\$3,
CAWA18A0A	18,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, Wall T-stat	\$5,
CAWA20A0A	20,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, Wall T-stat	\$5,
CAWA33A0A	33,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, Wall T-stat	\$6,
CAWA36A0A	36,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, Wall T-stat	\$6,
CAWA08D0A	8,000 Btu/h, 208-230 V/1 ph/60 Hz, No Heat, Wall T-stat	\$3,
CAWA12D0A	12,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Wall T-stat	\$3,
CAWA18D0A	18,000 Btu/h,208-230 V/1 ph/ 60 Hz, No Heat, Wall T-stat	\$4,
CAWA20D0A	20,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Wall T-stat	\$4,
CAWA33D0A	33,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Wall T-stat	\$6,
CAWA36D0A	36,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Wall T-stat	\$6,
CAWA08F0A	8,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, Wall T-stat	\$3,
CAWA12F0A	12,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, Wall T-stat	\$3,
CAWA18F0A	18,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, Wall T-stat	\$4,
CAWA20F0A	20,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, Wall T-stat	\$4,
CAWA33F0A	33,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, Wall T-stat	\$6,
CAWA36F0A	36,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, Wall T-stat	\$6,
	2-Pipe Fan Coil Cassette Air Handlers with LED Display Lights - No Heat	Tra
ltem #	I/R Handheld Remote is included with the unit	Pr
CAWB08A0A	8,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, I/R Handheld Remote	\$4,
CAWB12A0A	12,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, I/R Handheld Remote	\$4,
CAWB18A0A	18,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, I/R Handheld Remote	\$5,
CAWB20A0A	20,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, I/R Handheld Remote	\$5,
CAWB33A0A	33,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, I/R Handheld Remote	\$7,
CAWB36A0A	36,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, I/R Handheld Remote	\$7,
CAWB08D0A	8,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, I/R Handheld Remote	\$3,
CAWB12D0A	12,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, I/R Handheld Remote	\$3,
CAWB12D0A	18,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, I/R Handheld Remote	\$4,
CAWB10D0A	20,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, I/R Handheld Remote	\$5,
CAWB33D0A	33,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, I/R Handheld Remote	\$6,
CAWB36D0A	36,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, I/R Handheld Remote	\$6,
CAWB08F0A	8,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote	\$3,
CAWB0010A	12,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote	\$3,
CAWB12F0A	18,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote	\$5,
CANDIOLOY	20,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote	\$5,
		γJ,
CAWB20F0A		ĊC
CAWB33F0A	33,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote	
CAWB33F0A CAWB36F0A	33,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote 36,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote	\$6, \$6,
CAWB33F0A CAWB36F0A 240004563	33,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote 36,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote 2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 3.5, Close-Off: 25 PSI	\$6, \$2
CAWB33F0A CAWB36F0A 240004563 240002421	33,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote 36,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote 2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 3.5, Close-Off: 25 PSI 3-Way NC Valve, 24 Vac Actuator, 1/2 in Sweat Connections, Cv: 4.0, Close-Off: 25 PSI	\$6, \$2 \$2
CAWB33F0A CAWB36F0A 240004563 240002421 240009598	33,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote 36,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote 2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 3.5, Close-Off: 25 PSI 3-Way NC Valve, 24 Vac Actuator, 1/2 in Sweat Connections, Cv: 4.0, Close-Off: 25 PSI 3-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 7.5, Close-Off: 17 PSI	\$6, \$2 \$2 \$3
CAWB33F0A CAWB36F0A 240004563 240002421 240009598 240009597	33,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote 36,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote 2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 3.5, Close-Off: 25 PSI 3-Way NC Valve, 24 Vac Actuator, 1/2 in Sweat Connections, Cv: 4.0, Close-Off: 25 PSI 3-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 7.5, Close-Off: 17 PSI 2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 7.5, Close-Off: 17 PSI	\$6, \$2 \$2 \$3 \$3 \$2
CAWB33F0A CAWB36F0A 240004563 240002421 240009598 240009597 240009597 240003614	33,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote 36,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote 2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 3.5, Close-Off: 25 PSI 3-Way NC Valve, 24 Vac Actuator, 1/2 in Sweat Connections, Cv: 4.0, Close-Off: 25 PSI 3-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 7.5, Close-Off: 17 PSI 2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 7.5, Close-Off: 17 PSI Fresh Air Duct Collar Kit, 3 in Ø, CAH/CAC/CAW, 3 Collars & 3 Plates	\$6, \$2 \$3 \$3 \$2 \$1
CAWB33F0A CAWB36F0A 240004563 240002421 240009598 240009597	33,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote 36,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, I/R Handheld Remote 2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 3.5, Close-Off: 25 PSI 3-Way NC Valve, 24 Vac Actuator, 1/2 in Sweat Connections, Cv: 4.0, Close-Off: 25 PSI 3-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 7.5, Close-Off: 17 PSI 2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 7.5, Close-Off: 17 PSI	

24 Vac -40 VA transformer standard on 2-pipe units. Control Voltage is 24 Vac. (only a 24 Vac valve can be used) Consult factory for lead times and minimum quantities.

Co	mfortwave Chilled Water Cassette Air Handlers (CAW)	
ltem #	2-Pipe Fan Coil Cassette Air Handlers - Electric Heat Wall Thermostat Operation Only (24 Vac wall thermostat sold separately)	Tra Pri
CAWA08D1A	8,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 1.5 kW Electric Heat, Wall T-stat	\$3,
CAWA12D1A	12,000 Btu/h,208-230 V/1 ph/ 60 Hz, 1.5 kW Electric Heat, Wall T-stat	\$3,
CAWA18D3A	18,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 3 kW Electric Heat, Wall T-stat	\$4,
CAWA20D3A	20,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 3 kW Electric Heat, Wall T-stat	\$5,
CAWA33D5A	33,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 5 kW Electric Heat, Wall T-stat	\$7,
CAWA36D5A	36,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 5 kW Electric Heat, Wall T-stat	\$7,
CAWA08F1A	8,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 1.5 kW Electric Heat, Wall T-stat	\$3,
CAWA12F1A	12,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 1.5 kW Electric Heat, Wall T-stat	\$3,
CAWA18F3A	18,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 3 kW Electric Heat, Wall T-stat	\$4,
CAWA20F3A	20,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 3 kW Electric Heat, Wall T-stat	\$5,
CAWA33F5A	33,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 5 kW Electric Heat, Wall T-stat	\$7,
CAWA36F5A	36,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 5 kW Electric Heat, Wall T-stat	\$7,
		-
ltem #	2-Pipe Fan Coil Cassette Air Handlers with LED Lights - Electric Heat	Tra Pr
	I/R Handheld Remote is included with the unit	
CAWB08D1A	8,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 1.5 kW Electric Heat, I/R Handheld Remote	\$3,
CAWB12D1A	12,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 1.5 kW Electric Heat, I/R Handheld Remote	\$3,
CAWB18D3A	18,000 Btu/h,208-230 V/1 ph/ 60 Hz, 3 kW Electric Heat, I/R Handheld Remote	\$5,
CAWB20D3A	20,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 3 kW Electric Heat, I/R Handheld Remote	\$5,
CAWB33D5A CAWB36D5A	33,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 5 kW Electric Heat, I/R Handheld Remote	\$7,
CAWB36D5A CAWB08F1A	36,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 5 kW Electric Heat, I/R Handheld Remote	\$7,
	8,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 1.5 kW Electric Heat, I/R Handheld Remote	\$3,
CAWB12F1A	12,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 1.5 kW Electric Heat, I/R Handheld Remote	\$3,
CAWB18F3A	18,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 3 kW Electric Heat, I/R Handheld Remote	\$5,
CAWB20F3A	20,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 3 kW Electric Heat, I/R Handheld Remote	\$5,
CAWB33F5A CAWB36F5A	33,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 5 kW Electric Heat, I/R Handheld Remote 36,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 5 kW Electric Heat, I/R Handheld Remote	\$7, \$7,
CAWD30F5A	36,000 blu/ii, 220-240 V/1 pii/ 30 nz, 3 kW Electric neat, i/k haliulielu keliiote	Ş1,
Part #	Optional Accessories Descriptions	Tra Pr
240004563	2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 3.5, Close-Off: 25 PSI	\$2
240002421	3-Way NC Valve, 24 Vac Actuator, 1/2 in Sweat Connections, Cv: 4.0, Close-Off: 25 PSI	\$2
240009598	3-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 7.5, Close-Off: 17 PSI	\$3
240009597	2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 7.5, Close-Off: 17 PSI	\$2
240003614	Fresh Air Duct Collar Kit, 3 in Ø, CAH/CAC/CAW, 3 Collars & 3 Plates	\$1
240009786	Discharge/Branch Duct Collar Kit, 5 in Ø, All CAH/C/W & CAF08-20 Models, Qty 2 Pcs.	\$1
240003106	Condensate Pump Kit, 208-230 V, 144 in Lift, External Floor Mount, Field-installed	\$1
240003107	Condensate Pump Kit, 115 V, 144 in Lift, External Floor Mount, Field-installed	\$1
550003770	MERV 8 Filter Kit CAW 08/12	\$
550003771	MERV 8 Filter Kit CAW 18/20	\$
550003772	MERV 8 Filter Kit CAW 33/36	\$

24 Vac -40 VA transformer standard on 2-pipe units. Control Voltage is 24 Vac. (Only a 24 Vac valve can be used) Consult factory for lead times and minimum quantities.

	Comfortwave Cassette Air Handlers (CAW)	
Item #	4-Pipe Fan Coil Cassette Air Handlers - Hydronic Heat Wall Thermostat Operation Only (24 Vac wall thermostat sold separately)	Trade Price
CAWA08A8A	8,000 Btu/h, 115 V/1 ph/ 60 Hz, Hydronic Heat, Wall T-stat	\$4,696
CAWA12A8A	12,000 Btu/h, 115 V/1 ph/ 60 Hz, Hydronic Heat, Wall T-stat	\$4,902
CAWA18A8A	18,000 Btu/h, 115 V/1 ph/ 60 Hz, Hydronic Heat, Wall T-stat	\$6,069
CAWA20A8A	20,000 Btu/h, 115 V/1 ph/ 60 Hz, Hydronic Heat, Wall T-stat	\$6,256
CAWA33A8A	33,000 Btu/h, 115 V/1 ph/ 60 Hz, Hydronic Heat, Wall T-stat	\$8,431
CAWA36A8A	36,000 Btu/h, 115 V/1 ph/ 60 Hz, Hydronic Heat, Wall T-stat	\$8,619
CAWA08D8A	8,000 Btu/h, 208-230 V/1 ph/ 60 Hz, Hydronic Heat, Wall T-stat	\$4,349
CAWA12D8A	12,000 Btu/h, 208-230 V/1 ph/ 60 Hz, Hydronic Heat, Wall T-stat	\$4,538
CAWA18D8A	18,000 Btu/h, 208-230 V/1 ph/ 60 Hz, Hydronic Heat, Wall T-stat	\$5,619
CAWA20D8A	20,000 Btu/h, 208-230 V/1 ph/ 60 Hz, Hydronic Heat, Wall T-stat	\$5,808
CAWA33D8A	33,000 Btu/h, 208-230 V/1 ph/ 60 Hz, Hydronic Heat, Wall T-stat	\$7,807
CAWA36D8A	36,000 Btu/h, 208-230 V/1 ph/ 60 Hz, Hydronic Heat, Wall T-stat	\$7,980
CAWA08F8A	8,000 Btu/h, 220-240 V/1 ph/ 50 Hz, Hydronic Heat, Wall T-stat	\$4,349
CAWA12F8A	12,000 Btu/h, 220-240 V/1 ph/ 50 Hz, Hydronic Heat, Wall T-stat	\$4,538
CAWA18F8A	18,000 Btu/h, 220-240 V/1 ph/ 50 Hz, Hydronic Heat, Wall T-stat	\$5,619
CAWA20F8A	20,000 Btu/h, 220-240 V/1 ph/ 50 Hz, Hydronic Heat, Wall T-stat	\$5,808
CAWA33F8A	33,000 Btu/h, 220-240 V/1 ph/ 50 Hz, Hydronic Heat, Wall T-stat	\$7,807
CAWA36F8A	36,000 Btu/h, 220-240 V/1 ph/ 50 Hz, Hydronic Heat, Wall T-stat	\$7,980
		_
ltem #	4-Pipe Fan Coil Cassette Air Handlers with LED Lights - Hydronic Heat	Trade
item #	I/R Handheld Remote is included with the unit	Price
CAWB08A8A	8,000 Btu/h, 115 V/1 ph/ 60 Hz, Hydronic Heat, I/R Handheld Remote	\$5,165
CAWB12A8A	12,000 Btu/h, 115 V/1 ph/ 60 Hz, Hydronic Heat, I/R Handheld Remote	\$5,391
CAWB18A8A	18,000 Btu/h, 115 V/1 ph/ 60 Hz, Hydronic Heat, I/R Handheld Remote	\$6,675
CAWB20A8A	20,000 Btu/h, 115 V/1 ph/ 60 Hz, Hydronic Heat, I/R Handheld Remote	\$7,006
CAWB33A8A	33,000 Btu/h, 115 V/1 ph/ 60 Hz, Hydronic Heat, I/R Handheld Remote	\$9,274
CAWB36A8A	36,000 Btu/h, 115 V/1 ph/ 60 Hz, Hydronic Heat, I/R Handheld Remote	\$9,480
CAWB08D8A	8,000 Btu/h, 208-230 V/1 ph/ 60 Hz, Hydronic Heat, I/R Handheld Remote	\$4,783
CAWB12D8A	12,000 Btu/h, 208-230 V/1 ph/ 60 Hz, Hydronic Heat, I/R Handheld Remote	\$4,991
CAWB18D8A	18,000 Btu/h, 208-230 V/1 ph/ 60 Hz, Hydronic Heat, I/R Handheld Remote	\$6,181
CAWB20D8A	20,000 Btu/h, 208-230 V/1 ph/ 60 Hz, Hydronic Heat, I/R Handheld Remote	\$6,488
CAWB33D8A	33,000 Btu/h, 208-230 V/1 ph/ 60 Hz, Hydronic Heat, I/R Handheld Remote	\$8,588
CAWB36D8A	36,000 Btu/h, 208-230 V/1 ph/ 60 Hz, Hydronic Heat, I/R Handheld Remote	\$8,778
CAWB08F8A	8,000 Btu/h, 220-240 V/1 ph/ 50 Hz, Hydronic Heat, I/R Handheld Remote	\$4,783
CAWB12F8A	12,000 Btu/h, 220-240 V/1 ph/ 50 Hz, Hydronic Heat, I/R Handheld Remote	\$4,991
CAWB18F8A	18,000 Btu/h, 220-240 V/1 ph/ 50 Hz, Hydronic Heat, I/R Handheld Remote	\$6,181
CAWB20F8A	20,000 Btu/h, 220-240 V/1 ph/ 50 Hz, Hydronic Heat, I/R Handheld Remote	\$6,488
CAWB33F8A	33,000 Btu/h, 220-240 V/1 ph/ 50 Hz, Hydronic Heat, I/R Handheld Remote	\$8,588
	36,000 Btu/h, 220-240 V/1 ph/ 50 Hz, Hydronic Heat, I/R Handheld Remote	\$8,778

Comfortwave Cassette Air Handlers (CAW)

Part #	CAW - Optional Accessories Descriptions	Trade Price
240008208	24 Vac Single Stage, Heat/Cool, 7-Day Programmable, Manual Changeover Thermostat	\$98
240008210	24 Vac Single Stage, Heat/Cool, 7-Day Programmable, Auto Changeover Thermostat	\$177
240006566	Infrared Handheld Remote Controller w/ Wall-Mount Cradle, CAW	\$255
240004563	2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 3.5, Close-Off: 25 PSI	\$255
240002421	3-Way NC Valve, 24 Vac Actuator, 1/2 in Sweat Connections, Cv: 4.0, Close-Off: 25 PSI	\$252
240009598	3-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 7.5, Close-Off: 17 PSI	\$303
240009597	2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Connections, Cv: 7.5, Close-Off: 17 PSI	\$284
240003614	Fresh Air Duct Collar Kit, 3 in Ø, CAW, 3 Collars & 3 Plates	\$197
240009786	Discharge/Branch Duct Collar Kit, 5 in Ø, All CAW Models, Qty 2 Pcs.	\$195
240003106	Condensate Pump, 208-230 V, 144 in Lift, External Floor Mount, Field-installed	\$127
240003107	Condensate Pump, 115 V, 144 in Lift, External Floor Mount, Field-installed	\$127

Control Voltage=24 Vac (Only 24 Vac valve can be used)

24 Vac -40 VA transformer standard on 2-pipe, **Infrared hand held controller is included with the CAWB cassette with IR controller option "B". 24 Vac T'stat SOLD SEPARATELY**

Consult factory for lead times and minimum quantities.

- CAW Infrared Controls include:
- Hand held Infrared Controller
- High/low fan speed w/ auto ramp, constant fan
- Non volatile memory, auto re-start after power outage
- Anti-Short Cycle timer
- Dry Mode
- Internal condensate pump w/ 36 in lift

CAW Wall Thermostat controls include:


- 24 Vac remote thermostat connection
- Electronic control with anti short cycle and post purge timer
- Internal Condensate pump w/ 36 in lift

Options include:


- Electric heat or hot water hydronic heat
- Condensate pump independently wired (144 in lift), externally mounted
- 115/1/60 Voltage
- 220/240/1/50 Voltage

One Year Parts Warranty

Comfortwave Ceiling-Suspended Air Handler (CCP) Decoding



Comfortwave High-Wall Air Handler (WCP) Decoding







CCP/WCP Ceiling Suspended (CCP) & High Wall (WCP) Air Handlers

com

CCP Ceiling-Suspended Air Handler

- 8,000 48,000 Btu/h Capacities
- 208-230 V/1 ph/ 60 Hz Standard
- 115 V/1 ph/ 60 Hz Available
- 220-240 V/1 ph/ 50 Hz Available
- 4 Chassis Sizes:
 - 12 (~9/12/15 kBtu/h)
 - 24 (~18/24 kBtu/h)
 - 30 (~30 kBtu/h)
 - 48 (~36/42/48 kBtu/h)
- 24 Vac Remote Thermostat Configuration
- Infrared Handheld Remote Control Option
 Remote Sold Separately
- Washable Return Air Filter(s)
- 2-Pipe Applications Allow for Optional Factory Installed Electric Heat:
 - 3 kW (9/12/15 kBtu/h)
 - 5 kW (18/24/30 kBtu/h)
 - 7 kW (48 kBtu/h)
- 4-Pipe Applications, Hydronic Cooling & Heating
- Adjustable, Plastic Discharge Air Grille
- Condensate pump harness Plug & Play connection (Optional) Pump - 48' lift internal or external mount plug & Play
 Condensate Play
 - (Optional) Pump 144' lift, external mount - independently wired

WCP High Wall Air Handler

- 9,000 30,000 Btu/h Capacities
- 208-230 V/1 ph/ 60 Hz Standard
- 115 V/1 ph/ 60 Hz Available
- 220-240 V/1 ph/ 50 Hz Available
- 3 Chassis Sizes:
- 12 (~9/12 kBtu/h)
- 18 (~15/18 kBtu/h)
- 30 (~24/30 kBtu/h)
- 24 Vac Remote Thermostat Configuration
- Infrared Handheld Remote Control Option
 Remote Sold Separately
- Washable Return Air Filter(s)
- 2-Pipe Applications Allow for Optional Factory Installed Electric Heat:
 - 3 kW (9/12/15/18 kBtu/h)
 - 5 kW (24/30 kBtu/h)
- Adjustable, Plastic Discharge Air Grille
- Condensate pump harness Plug & Play connection (Optional) Pump - 48 in lift internal or external mount - plug & Play
 - (Optional) Pump 144 in lift, external mount
 - independently wired





WCP



CCP/WCP Remote Control (Sold Seperately)



Standard 1-year parts

5-year compressor warranty

Model	Shipping Weights	
CCP 09/12	115 lb	52.2 kg
CCP 18/24/30	135 lb	61.2 kg
CCP 36/42/48	160 lb	72.6 kg
WCP09	85 lb	38.6 kg
WCP12	85 lb	38.6 kg
WCP15	115 lb	52.2 kg
WCP18	115 lb	52.2 kg
WCP24	115 lb	52.2 kg
WCP30	115 lb	52.2 kg

Comfortwave Fan Coil Control Descriptions (CCP & WCP)

Unit / Control Type	Description
CCP & WCP Models Wall Thermostat Controlled Units - Thermostat is Not Included (purchased separately)	Unit will not have a unit mounted control panel. Choose 24 Vac, dry contact type thermostat. EMI equipment is compatible with most standard bimetal, digital electronic or power-stealing thermostats. Chilled Water Cooling Only - select a thermostat compatible with chilled water cooling system and the chilled water valve selected. Thermostat should have "R", "Y" and "G" terminals. Thermostat may also have a "C" terminal. Chilled Water with Electric or Hot Water (Hydronic) Heat - Select thermostat compatible with chilled water cooling and hot water or electric heating systems with water valve(s) selected. Thermostat should have "R", "Y", "W" and "G" terminals. Thermostat may also have "C" terminal. WHEN SELECTING WALL THERMOSTAT UNITS THEY ARE NOT CONVERTABLE TO OPERATE WITH AN IR REMOTE CONTROL. WCP unit is equipped with a Hi/Low fan speed switch
Unit Mounted Controlled Units - IR handheld remote is not included (purchased separately) INFRARED REMOTE CONTROL OPTION OFERATIONAL RANGE 55-50° F (M 1* DECREMENTE) OFERATIONAL RANGE 55-50° F (M 1* DE	Unit Mounted Control Panel With LED display and operational controls

	Comfortwave Ceiling-Suspended Air Handlers (CCP)	
	2-Pipe Ceiling-Suspended Chilled Water Air Handlers - No Heat	Trade
Item #	Wall Thermostat Operation Only (24 Vac wall thermostat sold separately)	Price
CCP12A001AA0B0A	9,000-12,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, Wall T-Stat	\$5,528
CCP12D001AA0B0A	9,000-12,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Wall T-Stat	\$5,528
CCP24D001AA0B0A	18,000-24,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Wall T-Stat	\$6,029
CCP30D001AA0B0A	30,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Wall T-Stat	\$6,117
CCP48D001AA0B0A	36,000-48,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Wall T-Stat	\$6,347
CCP12F001AA0B0A	9,000-12,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Elec Heat, Wall T-Stat	\$5,528
CCP24F001AA0B0A	18,000-24,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Elec Heat, Wall T-Stat	\$6,029
CCP30F001AA0B0A	30,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Elec Heat, Wall T-Stat	\$6,117
CCP48F001AA0B0A	36,000-48,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Elec Heat, Wall T-Stat	\$6,347
	2-Pipe Ceiling-Suspended Chilled Water Wall Air Handlers - No Heat	Trade
ltem #	Unit Mounted Controller	Price
	IR Remote Compatible (handheld remote sold separately)	FILE
CCP12A041AA0B0A	9,000-12,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$5,634
CCP12D041AA0B0A	9,000-12,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$5,634
CCP24D041AA0B0A	18,000-24,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$6,135
CCP30D041AA0B0A	30,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$6,223
CCP48D041AA0B0A	36,000-48,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$7,142
CCP12F041AA0B0A	9,000-12,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$5,634
CCP24F041AA0B0A	18,000-24,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$6,135
CCP30F041AA0B0A	30,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$6,223
CCP48F041AA0B0A	36,000-48,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$7,142
ltem #	2-Pipe Ceiling-Suspended Chilled Water Air Handlers - Electric Heat	Trade
itein#	Wall Thermostat Operation Only (24 Vac wall thermostat sold separately)	Price
CCP12A301AA0B0A	9,000-12,000 Btu/h, 115 V/1 ph/ 60 Hz, 0.75 kW Elec Heat, Wall T-Stat	\$5,865
CCP12D301AA0B0A	9,000-12,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 3 kW Elec Heat, Wall T-Stat	\$5,865
CCP24D501AA0B0A	18,000-24,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 5 kW Elec Heat, Wall T-Stat	\$6,365
CCP30D501AA0B0A	30,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 5 kW Elec Heat, Wall T-Stat	\$6,453
CCP48D701AA0B0A	36,000-48,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 7 kW Elec Heat, Wall T-Stat	\$6,683
CCP12F301AA0B0A	9,000-12,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 3 kW Elec Heat, Wall T-Stat	\$5,865
CCP24F501AA0B0A	18,000-24,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 5 kW Elec Heat, Wall T-Stat	\$6,365
CCP30F501AA0B0A	30,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 5 kW Elec Heat, Wall T-Stat	\$6,453
CCP48F701AA0B0A	36,000-48,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 7 kW Elec Heat, Wall T-Stat	\$6,683
	2-Pipe Ceiling-Suspended Chilled Water Air Handlers - Electric Heat	Trade
ltem #	Unit Mounted Controller	Price
	IR Remote Compatible (handheld remote sold separately)	
CCP12A341AA0B0A	9,000-12,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 0.75 kW Elec Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$5,965
CCP12D341AA0B0A	9,000-12,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 3 kW Elec Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$5,965
CCP24D541AA0B0A	18,000-24,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 5 kW Elec Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$6,465
CCP30D541AA0B0A	24,000-30,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 5 kW Elec Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$6,553
CCP48D741AA0B0A	36,000-48,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 7 kW Elec Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$7,490
CCP12F341AA0B0A	9,000-13,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 3 kW Elec Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$5,965
CCP24F541AA0B0A	18,000-24,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 5 kW Elec Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$6,465
CCD20EE 41 4 4 0 D 0 4	30,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 5 kW Elec Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$6,553
CCP30F541AA0B0A CCP48F741AA0B0A	36,000 -48,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 7 kW Elec Heat, Unit-Mount Ctrls, Handheld Remote Compatible	

	Comfortwave Ceiling-Suspended Air Handlers (CCP)	
ltem #	4-Pipe Ceiling-Suspended Chilled Water Air Handlers - Hydronic Heat Wall Thermostat Operation Only (24 Vac wall thermostat sold separately	Trade Price
CCP12A801AA0B0A	9,000-12,000 Btu/h, Hydronic Heat, 115 V/1 ph/ 60 Hz, Wall T-Stat	\$5,906
CCP12D801AA0B0A	9,000-12,000 Btu/h, Hydronic Heat, 208-230 V/1 ph/ 60 Hz, Wall T-Stat	\$5,906
CCP24D801AA0B0A	18,000-24,000 Btu/h, Hydronic Heat, 208-230 V/1 ph/ 60 Hz, Wall T-Stat	\$7,843
CCP30D801AA0B0A	30,000 Btu/h, Hydronic Heat, 208-230 V/1 ph/ 60 Hz, Wall T-Stat	\$7,936
CCP48D801AA0B0A	36,000-48,000 Btu/h, Hydronic Heat, 208-230 V/1 ph/ 60 Hz, Wall T-Stat	\$7,590
CCP12F801AA0B0A	9,000-12,000 Btu/h, Hydronic Heat, 220-240 V/1 ph/ 50 Hz, Wall T-Stat	\$5,906
CCP24F801AA0B0A	18,000-24,000 Btu/h, Hydronic Heat, 220-240 V/1 ph/ 50 Hz, Wall T-Stat	\$7,843
CCP30F801AA0B0A	30,000 Btu/h, Hydronic Heat, 220-240 V/1 ph/ 50 Hz, Wall T-Stat	\$7,936
CCP48F801AA0B0A	36,000-48,000 Btu/h, Hydronic Heat, 220-240 V/1 ph/ 50 Hz, Wall T-Stat	\$7,590
	4-Pipe Ceiling-Suspended Chilled Water Wall Air Handlers - Hydronic Heat	Trada
Item #	Unit Mounted Controller	Trade Price
	IR Remote Compatible (handheld remote sold separately)	FILE
CCP12A841AA0B0A	9,000-12,000 Btu/h, 115 V/1 ph/ 60 Hz, Hydronic Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$6,019
CCP12D841AA0B0A	9,000-12,000 Btu/h, 208-230 V/1 ph/ 60 Hz, Hydronic Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$6,066
CCP24D841AA0B0A	18,000-24,000 Btu/h, 208-230 V/1 ph/ 60 Hz, Hydronic Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$8,237
CCP30D841AA0B0A	30,000 Btu/h, 208-230 V/1 ph/ 60 Hz, Hydronic Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$8,332
CCP48D841AA0B0A	36,000-48,000 Btu/h, 208-230 V/1 ph/ 60 Hz, Hydronic Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$8,249
CCP12D841AA0B0A	9,000-12,000 Btu/h, 220-240 V/1 ph/ 50 Hz, Hydronic Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$6,066
CCP24D841AA0B0A	18,000-24,000 Btu/h, 220-240 V/1 ph/ 50 Hz, Hydronic Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$8,237
CCP30D841AA0B0A	30,000 Btu/h, 220-240 V/1 ph/ 50 Hz, Hydronic Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$8,332
CCP48D841AA0B0A	36,000-48,000 Btu/h, 220-240 V/1 ph/ 50 Hz, Hydronic Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$8,249
Part #	Optional Accessories Descriptions (CCP)	Trade Price
240008208	24 Vac Single Stage, Heat/Cool, Programmable, Manual Changeover Thermostat	\$98
240008210	24 Vac Single Stage, Heat/Cool, Programmable, Auto Changeover Thermostat	\$177
240003455	Infrared Handheld Remote Controller w/ Wall Cradle (Unit-Mount Controlled Units Only)	\$141
240004563	2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Conn, Cv: 3.5, Close-Off: 25 PSI	\$255
240002421	3-Way NC Valve, 24 Vac Actuator, 1/2 in Sweat Conn, Cv: 4.0, Close-Off: 25 PSI	\$252
240009598	3-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Conn, Cv: 7.5, Close-Off: 17 PSI	\$303
240009597	2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Conn, Cv: 7.5, Close-Off: 17 PSI	\$284
550000339	CCP Trim Kit, 12-30, Mount Covers	\$341
550000340	CCP Trim Kit, 36-48, Mount Covers	\$197
550003440	Condensate Pump 09-48, 115/208/230 Vac, Field-installed, 48 in Lift, Internal Mount	\$656
240003106	Condensate Pump Kit, 144 in lift, 208/230 Vac, External Floor Mount, Field-installed	\$127
240003107	Condensate Pump Kit, 144 lift, 115 Vac, External Floor Mount, Field-installed	\$127

Control Voltage = 24 Vac (Only 24 Vac valve can be used)

24 Vac - 40 VA transformer standard on 2-pipe, thermostat not included

Consult factory for lead times on all models hot water Heat option and minimum quantities.

Hot water Heat can only be ordered as supplemental Heat.

PRODUCT INFORMATION

Comfort Features: Optional 24 Vac wall thermostat (not included); fresh air knockout. *Installation & Service:* 208-230 Vac standard voltage. One year parts warranty.

	Comfortwave High-Wall Air Handlers (WCP)	
	2-Pipe Chilled Water High-Wall Air Handlers - No Heat	Trade
ltem #	Wall Thermostat Operation Only (24 Vac wall thermostat sold separately)	Price
WCP12A010AA0B0A	9,000-12,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, Wall T-Stat	\$3,291
WCP18A010AA0B0A	15,000-18,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, Wall T-Stat	\$3,827
WCP30A010AA0B0A	24,000-30,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, Wall T-Stat	\$4,574
WCP12D010AA0B0A	9,000-12,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Wall T-Stat	\$3,327
WCP18D010AA0B0A	15,000-18,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Wall T-Stat	\$3,798
WCP30D010AA0B0A	24,000-30,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Wall T-Stat	\$4,563
WCP12F010AA0B0A	9,000-12,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, Wall T-Stat	\$3,327
WCP18F010AA0B0A	15,000-18,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, Wall T-Stat	\$3,827
WCP30F010AA0B0A	24,000-30,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, Wall T-Stat	\$4,574
	2-Pipe Chilled Water High-Wall Air Handlers - No Heat	Trade
ltem #	Unit Mounted Controller	Price
	IR Remote Compatible (handheld remote sold separately)	
WCP12A000AA0B0A	9,000-12,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$3,487
WCP18A000AA0B0A	15,000-18,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$4,181
WCP30A000AA0B0A	24,000-30,000 Btu/h, 115 V/1 ph/ 60 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$4,770
WCP12D000AA0B0A	9,000-12,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$3,593
WCP18D000AA0B0A	15,000-18,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$4,092
WCP30D000AA0B0A	24,000-30,000 Btu/h, 208-230 V/1 ph/ 60 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$4,799
WCP12F000AA0B0A	9,000-12,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$3,593
WCP18F000AA0B0A	15,000-18,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$4,181
WCP30F000AA0B0A	24,000-30,000 Btu/h, 220-240 V/1 ph/ 50 Hz, No Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$4,770
ltem #	2-Pipe Chilled Water High-Wall Air Handlers - Electric Heat	Trade
	Wall Thermostat Operation Only (24 Vac wall thermostat sold separately)	Price
WCP12A310AA0B0A	9,000-12,000 Btu/h, 115 V/1 ph/ 60 Hz, 0.75 kW Elec Heat, Wall T-Stat	\$3,727
WCP18A310AA0B0A	15,000-18,000 Btu/h, 115 V/1 ph/ 60 Hz, 0.75 kW Elec Heat, Wall T-Stat	\$4,292
WCP30A510AA0B0A	24,000-30,000 Btu/h, 115 V/1 ph/ 60 Hz, 1.25 kW Elec Heat, Wall T-Stat	\$5,093
WCP12D310AA0B0A	9,000-12,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 3 kW Elec Heat, Wall T-Stat	\$3,620
WCP18D310AA0B0A	15,000-18,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 3 kW Elec Heat, Wall T-Stat	\$4,115
WCP30D510AA0B0A	24,000-30,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 5 kW Elec Heat, Wall T-Stat	\$4,821
WCP12F310AA0B0A WCP18F310AA0B0A	9,000-12,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 3 kW Elec Heat, Wall T-Stat 15,000-18,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 3 kW Elec Heat, Wall T-Stat	\$3,620 \$4,292
WCP30F510AA0B0A	24,000-30,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 5 kW Elec Heat, Wall T-Stat	\$4,821
WCI SUI SIONAUBUA	2-Pipe Chilled Water High-Wall Air Handlers - Electric Heat	,021
ltem #	Unit Mounted Controller	Trade
itein #	IR Remote Compatible (handheld remote sold separately)	Price
WCP12A300AA0B0A	9,000-12,000 Btu/h, 115 V/1 ph/ 50 Hz, 0.75 kW Elec Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$3,727
WCP18A300AA0B0A	15,000-18,000 Btu/h, 115 V/1 ph/ 60 Hz, 0.75 kW Elec Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$4,292
WCP30A500AA0B0A	24,000-30,000 Btu/h, 115 V/1 ph/ 60 Hz, 1.25 kW Elec Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$5,093
WCP12D300AA0B0A	9,000-12,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 3 kW Elec Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$3,845
WCP18D300AA0B0A	15,000-18,000 Btu/h, 208-/230 V/1 ph/ 60 Hz, 3 kW Elec Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$4,292
WCP30D500AA0B0A	24,000-30,000 Btu/h, 208-230 V/1 ph/ 60 Hz, 5 kW Elec Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$5,175
WCP12F300AA0B0A	9,000-12,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 3 kW Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$3,845
WCP18F300AA0B0A	15,000-18,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 3 kW Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$4,292
WCP30F500AA0B0A	24,000-30,000 Btu/h, 220-240 V/1 ph/ 50 Hz, 5 kW Heat, Unit-Mount Ctrls, Handheld Remote Compatible	\$5,175

Comfortwave High-Wall Air Handlers (WCP)		
Part #	WCP - Optional Accessories Descriptions	Trade Price
240008208	24 Vac Single Stage, Heat/Cool, 7-Day Programmable, Manual Changeover Thermostat	\$98
240008210	24 Vac Single Stage, Heat/Cool, 7-Day Programmable, Auto Changeover Thermostat	\$177
240003455	Infrared Handheld Remote Controller w/ Wall Cradle (Unit-Mount Controlled Units Only)	\$141
240004563	2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Conn, Cv: 3.5, Close-Off: 25 PSI	\$255
240002421	3-Way NC Valve, 24 Vac Actuator, 1/2 in Sweat Conn, Cv: 4.0, Close-Off: 25 PSI	\$252
240009598	3-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Conn, Cv: 7.5, Close-Off: 17 PSI	\$303
240009597	2-Way NC Valve, 24 Vac Actuator, 3/4 in Sweat Conn, Cv: 7.5, Close-Off: 17 PSI	\$284
550003439	Condensate Pump 09-30 115/208/230 Vac Field-installed, 48 in, Internal Mount	\$694
240003106	Condensate Pump Kit, 144 in lift, 208/230 Vac, External Floor Mount, Field-installed	\$127
240003107	Condensate Pump Kit, 144 in lift, 115 Vac, External Floor Mount, Field-installed	\$127

Control Voltage=24 Vac (Only 24 Vac valve can be used)

24 Vac-40 VA transformer standard on 2-pipe, 24 Vac thermostat not included

Consult factory for lead times and minimum quantities.

PRODUCT INFORMATION

WCP Unit Mounted controls include:

- High/low fan speed w/ auto ramp and post purge
- Non volatile memory, auto re-start after power outage
- Anti-Short Cycle timer
- Dry Mode
- Condensate pump harness ready connection

WCP Wall Thermostat controls include:

- 24 Vac remote thermostat connection
- Hi/Low Fan speed switch
- Electronic control with anti short cycle and post purge timer
- Condensate pump harness ready connection

Options include:

- Electric heat
- Condensate pump Plug & Play (48 in lift), internally or externally mount, field installed
- Condensate pump independently wired (144 in lift), externally mounted
- 115/1/60 Voltage
- 220/240/1/50 Voltage

Standard voltage all units (208/230/1/60)

One year parts warranty

TERMS & CONDITIONS OF SALE - GENERAL TERMS

PRICES & SPECIFICATIONS: All pricing and specifications subject to change without notice. The prices herein supersede all prior quotations, promotions and addendums.

ORDERS: All EMI orders will be accepted on the basis of prices in effect at the time the order is received. No order or contract will become an obligation on our part until accepted by the General Sales Department. ECR International shall not be liable for any delay, or failure in the delivery or shipment of goods, due to any cause or causes beyond its control.

All Buy American products are considered Special Order Products and are cited within this Price Book. Once such a special order has been accepted and acknowledged by the General Sales Department, a 100% cancellation fee will apply. On the order/PO, the customer must state the order is "Firm and Non-Cancellable"; otherwise ECR will not process it.

LEAD TIMES: EMI Comfortwave products are non-inventory items. Production lead times normally run 3 to 4 weeks. Customers are encouraged to check with the factory for specific model availability.

LARGE JOBS: Please consult factory for pricing and availability for any special-order models or more than 10 systems.

TAXES: Add to the prices and terms quoted any manufacturers' or sales tax payable on the transaction under any effective statute. All orders must include sales tax or resale certificate of sales tax exemption (If not already on file).

SHIPMENTS

TRUCK LOADS: \$50,000 Net order value or 25 systems - Freight Prepaid

F.O.B. ECR INTERNATIONAL - FACTORY OR WAREHOUSE

SALES ORDER INFORMATION CHECK LIST

The following information must be included on equipment or parts orders to insure proper shipment & invoicing:

1) Purchase Order Number 7) Pricing 8) 2) Bill to Address Product Description (Model, Size, etc.) 3) Ship to Address 9) Electrical (Operating Voltage, Cycles, Phases, etc.) 4) Method of Shipment (trailer load, UPS) 10) Non-Standard Equipment (Indicate "Optional" when **Requested Ship Date** substituted for standard equipment at extra cost listed. 5) Indicate added to standard equipment.) Kits or Parts (Orders for kits or parts must indicate 11) 6) Special Instructions ("Carrier to call...") equipment size and series.) Send orders to: E-mail: ecrorderentry@ecrinternational.com (315) 724-9319 Fax:

Please note the following Remit to Address:

Eax: (315) 724-9319 ECR International, Inc. P.O. Box 8000 Department 039 Buffalo, NY 14267

U.S. DISTRIBUTOR - RETURN MATERIAL POLICY

Prior Approval Required - All returns for <u>exchange</u>, <u>credit</u>, <u>repair service or warranty claim</u> must be approved by ECR International and require an RMA number prior to return of the material. A request must be completed via the online web portal. Please log on to www.ecrcustomerportal.com to complete your request for return. If you do not already have access to the customer web portal, please contact ECR International Customer Service at 1-800-325-5479 to be set-up.

Eligibility – An RMA Request must be received within 60 days from the date of invoice for returns of New & Unused product in original packaging. A restocking fee of 15% will be charged for all new and unused returns that are approved for return. Special Order Products (items not offered as standard in ECR International trade price book) are not eligible for return as new and unused product. Request for Warranty Returns must be made within the period covered by the warranty and must fall under the terms and conditions specified in the warranty.

Repair Service - Request for repair or rework of product damaged by customer is classified as Repair Service. Repair Service is billed at \$75.00 per hour for labor and net price for parts used in repair/rework. ECR International's Return Material (RM) department will evaluate the items returned for repair service. The customer will receive an estimate for the dollar amount, determined by ECR International's RM department, required to complete the repairs requested. A Purchase Order (PO) from the customer for that amount will be required before any work is performed.

RMA Expiration Parts - Once the RMA number is issued, the product must be returned within 60 days of the RMA date, or the RMA will be canceled. Products approved for return that are received after 60 days from the RMA date will not be accepted.

Shipping & Packaging - All returns must have a valid RMA number clearly displayed on the exterior of the package or the package will not be accepted. All returns of new and unused product must be in the original packaging. All returns must be shipped prepaid by the customer unless otherwise directed by ECR as indicated on the RMA Verification. Ship all approved return material to the facility indicated on the approved RMA Request by the date indicated.

Replacement Product - If replacement product is desired it must be indicated on the RMA Request. A PO# is required for the replacement shipment and must be indicated on the RMA Request. All replacement products will be invoiced at the time of shipment. ECR will pay the ground freight for all warranty replacements.

Application of Credit - Credit for returned product will be applied to the customer's account (less restocking fees for New and Unused returns) only after confirmation of receipt by ECR and inspection of the product. Issuance of a credit for a partial return of product does not relieve the customer from the obligation to remit payment for the merchandise not returned in accordance with the payment terms referenced on the customer's invoice(s). Customer will have the option to have any product that is denied for credit returned at their expense.

Returning Installed Finished Goods (Complete boilers, furnaces, A/C units etc.)

• Equipment that is already installed should be repaired not replaced. Exceptions: leaking cast iron boilers in their first year or leaking water tanks. Leaking drain valves on water tanks are replaceable, make sure the leak is not on the valve. Tanks returned with the only leak being on the valve will be denied.

• Cast iron blocks (not complete boilers) older than one year and Indirect tanks that are leaking do not require prior approval. Simply type "Leaking" into the Authorization field and it will be accepted. Complete Cast iron boilers within their first year will still require prior authorization for full boiler replacement.

• Water leaks on copper and condensing boilers are repairable and will require prior authorization for any reason for removal.

• To guarantee credit, if a situation arises where equipment does need to be replaced, *prior authorization* from ECR is required. This will ensure that ECR has visibility to the problem and has had an opportunity to correct it prior to removal. *All equipment considered for removal should first be brought to the attention of Technical Support at 1-800-253-7900*.

If approved, an authorization number will be given that will need to be entered in the RMA on the Customer Portal.
For equipment that is removed from service without prior authorization by ECR, contact Customer Service. They will evaluate the circumstance and can issue a conditional RMA. The equipment will be tested in our lab to determine if removal was warranted and if credit will be given.

RMA Expiration Equipment - Once the RMA number is issued, the product must be returned within 30 days of the RMA date, or the RMA will be canceled. Products approved for return that are received after 30 days from the RMA date will not be accepted.





Comfort Where It Counts

www.emiretroaire.com



All specifications subject to change without notice. ©2021 ECR International, Inc. PN 240011128 REV. D [07/13/2021]

BDR THERMEA GROUP